

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the above-identified application.

**Listing of Claims:**

Claims 1 to 55 (canceled)

56. (Currently amended) Dispensing unit for dispensing two fluid substances, comprising:

- a pump assembly having a first pump and a second pump, ~~which can be actuated~~ actuatable by ~~two a~~ a common, manually operable operating means ~~so that they to~~ simultaneously dispense the two fluid substances, and
- a reservoir assembly for holding the two fluid substances, the reservoir assembly comprising two integral reservoirs, which are each provided with an outlet at an outlet side and are each delimited by a movable piston on the side remote from the outlet, which pistons move towards the respective outlets during the dispensing of the fluid substances, characterized in that the reservoir assembly and the pump assembly are separate assemblies which ~~can be coupled~~ are couplable to one another, in such a manner that in the uncoupled state each reservoir ~~can be~~ is filled through the outlet of the reservoir, after which the pump assembly and the reservoir assembly are coupled to one another.

57. (Previously presented) Dispensing unit according to claim 56, wherein each piston prior to filling of the respective reservoir is located in a filling position close to the outlet.

58. (Previously presented) Dispensing unit according to claim 56, wherein a first reservoir is delimited by an inner side of a first substantially cylindrical tube, the reservoir being delimited, on the side remote from the outlet side, by a continuous, substantially disk-like piston.

59. (Previously presented) Dispensing unit according to claim 56, wherein a second reservoir is delimited by the outer side of the first cylindrical tube and an inner side of a second substantially cylindrical tube, which surrounds the first cylindrical tube, the reservoir being delimited, on the other side from the outlet side, by a continuous, substantially annular piston.

60. (Previously presented ) Dispensing unit according to claim 56, wherein the diameter or cross section of the first and/or second reservoir decreases in the direction of the outlet side over at least a section of the length of the reservoir.

61. (Previously presented) Dispensing unit according to claim 60, wherein the diameter of the inner side of the first cylindrical tube decreases in the direction of the outlet side.

62. (Previously presented) Dispensing unit according to claim 60, wherein the distance between the outer side of the first cylindrical tube and the inner side of the second cylindrical tube decreases in the direction of the outlet side.

63. (Previously presented) Dispensing unit according to claim 60, wherein the diameter of the inner side of the second cylindrical tube decreases in the direction of the outlet side, the outer side of the first cylindrical tube being straight.

64. (Previously presented) Dispensing unit according to claim 56, wherein the diameter or cross section of the first and/or second reservoir is increased at the abovementioned filling position in the vicinity of the outlet, in such a manner that the piston is under a reduced prestress in the abovementioned filling position in the vicinity of the outlet.

65. (Previously presented) Dispensing unit according to claim 64, wherein the diameter of the inner side of the first cylindrical tube, at the location of the piston position in the vicinity of the outlet, substantially corresponds to the diameter of the substantially disk-like piston.

66. (Previously presented) Dispensing unit according to claim 64, wherein the distance between the outer side of the first cylindrical tube and the inner side of the second cylindrical tube, at the location of the piston position in the vicinity of the outlet, substantially corresponds to the width of the ring of the substantially annular piston.

67. (Previously presented) Dispensing unit according to claim 56, wherein the reservoir assembly comprises a cover which closes off the reservoirs on the outlet side, the first and second outlets being arranged in the cover.

68. (Previously presented) Dispensing unit according to claim 67, wherein the cover is formed integrally with the second cylindrical tube.

69. (Previously presented) Dispensing unit according to claim 67, wherein the cover comprises a coupling rim for coupling a pump assembly to it in order to form a dispensing unit.

70. (Canceled)

71. (Previously presented) Dispensing unit according to claim 56, wherein the reservoir assembly further comprises a connecting element which connects the first and second cylindrical tubes to one another in the vicinity of those ends of the first and second cylindrical tubes which are remote from the outlet side.

72. (Previously presented) Dispensing unit according to claim 71, wherein the connecting element is formed integrally with the first cylindrical tube.

73. (Previously presented) Dispensing unit according to claim 67, wherein the cover is connected to the first and/or second cylindrical tube by means of a click-fit connection.

74. (Currently amended) Dispensing unit according to claim ~~67~~ 71, wherein the connecting element is connected to the first and/or second cylindrical tube by means of a click-fit connection.

Claims 75 to 81 (Canceled)

82. (Withdrawn) Dispensing unit for dispensing a first and a second fluid substance in a defined (volumetric) ratio, comprising:
- a first and a second reservoir for a stock of the first and second fluid substances, respectively,
  - a pump assembly, which comprises a first and a second pump which each have a pump chamber with a defined operative volume, and a common, manually operable operating member for actuating the first and second pumps, characterized in that the pump assembly comprises one or more exchangeable pump elements which form at least part of the first and/or second pump, so that the operative volume of the pump chamber of the first and/or second pump can be adjusted by selection of one or more suitable exchangeable pump elements and fitting of these elements in the pump assembly.
83. (Withdrawn) Dispensing unit according to claim 82, wherein the pump assembly also comprises a base part with a holding section for holding at least one of the exchangeable pump elements.

84. (Withdrawn) Dispensing unit according to claim 83, in which the holding section is designed to centre and/or position the at least one exchangeable pump element.
85. (Withdrawn) Dispensing unit according to claim 82, wherein the pump assembly comprises a first exchangeable pump element which is held in the base part and is coupled to the actuating member.
86. (Withdrawn) Dispensing unit according to claim 85, wherein the first and/or second pump is a bellows pump, the first exchangeable pump element at least partially forming a bellows pump chamber.
87. (Withdrawn) Dispensing unit according to claim 82, wherein the pump assembly comprises a first and a second exchangeable pump element, the first exchangeable pump element being coupled to the operating member and the second exchangeable pump element being held in the base part.
88. (Withdrawn) Dispensing unit according to claim 87, wherein the first and/or second pump is a piston pump, the first exchangeable pump element forming the piston of the first or second pump and the second exchangeable pump element forming the cylinder of the first or second pump.
89. (Withdrawn) Dispensing unit according to claim 88, wherein each pump is a piston pump, and in that the first exchangeable pump element forms both pistons and the second exchangeable pump element forms both cylinders.

90. (Withdrawn) Dispensing unit according to claim 88, wherein the first exchangeable pump element comprises a base surface, on which two cylindrical walls are arranged substantially at a right angle in order to form the pistons, and in that the second exchangeable pump element comprises a base plate on which two cylindrical walls are arranged substantially at a right angle in order to form the cylinders.
91. (Withdrawn) Dispensing unit according to claim 82, wherein the pump assembly is removably coupled to the first and/or second reservoir.
92. (Withdrawn) Dispensing unit according to claim 82, wherein the base part is provided with coupling means for optionally releasably coupling the pump assembly to the first and/or second reservoir.
93. (Withdrawn) Dispensing unit according to claim 82, wherein the first reservoir and the second reservoir are formed as a single entity.
94. (Withdrawn) Dispensing unit according to claim 82, wherein the first and second pumps are designed coaxially, in particular concentrically.
95. (Withdrawn) Dispensing unit according to claim 82, wherein the reservoirs are designed coaxially, in particular concentrically.

96. (Withdrawn) Dispensing unit according to claim 82, wherein the first and second reservoirs are of the "airless" type.
97. (Withdrawn) Dispensing unit for dispensing one fluid substance, comprising:
- at least one reservoir for a stock of fluid substance,
  - a pump assembly having at least one pump which has a pump chamber with a defined operative volume, and an easy-to-operate operating means for actuating the at least one pump, wherein the pump assembly comprises one or more exchangeable pump elements which form at least a section of the pump, so that the operative volume of the pump chamber of the pump can be adapted by selecting one or more suitable exchangeable pump elements and by fitting them in the pump assembly.
98. (Withdrawn) Dispensing unit according to claim 97, wherein the pump assembly also comprises a base part having a holding section for holding at least one of the exchangeable pump elements.
99. (Withdrawn) Dispensing unit according to claim 98 in which the holding part is designed to centre and/or position the first exchangeable pump element.
100. (Withdrawn) Dispensing unit according to claim 97, wherein the pump assembly comprises a first exchangeable pump element which is held in the base part and is coupled to the actuating member.



101. (Withdrawn) Dispensing unit according to claim 100, wherein the pump is a bellows pump, the first exchangeable pump element forming a bellows pump chamber.
102. (Withdrawn) Dispensing unit according to claim 97, wherein the pump assembly comprises a first and a second exchangeable pump element, the first exchangeable pump element being coupled to the operating member and the second exchangeable pump element being held in the base part.
103. (Withdrawn) Dispensing unit according to claim 102, wherein the pump is a piston pump, the first exchangeable pump element forming the piston of the pump and the second exchangeable pump element forming the cylinder of the pump.
104. (Withdrawn) Pump assembly clearly intended for a dispensing unit according to claim 97.
105. (Withdrawn) Method for the production of a dispensing unit according to claim 97, in which one or more suitable exchangeable pump elements are selected from a stock of different exchangeable pump elements as a function of the desired operative volume of the pump chamber of the first and/or second pump and are fitted in the pump assembly.

Application No.: 10/518,661  
Filing Date: July 5, 2005  
Attorney Docket No.: 903-125 PCT/US  
Amendment

**Amendments to the Drawings:**

The attached sheet 5 of the drawings includes changes to Fig. 6. Please replace sheet 5 of the drawings, as originally filed, with the attached sheet 5.

Attachment: Replacement Sheet 5 of the drawings